

ARCHITECTURAL
LINEAR DIFFUSER
CONCEALED MOUNTING
2-1/2" SLOT WIDTH

www.anemostat-hvac.com

PRODUCT FEATURES

- Linear slot diffuser for concealed mounting applications
- Internal controllers adjustable for pattern and volume control
- Alignment strips and mounting brackets furnished for field assembly and installation

CONSTRUCTION DETAILS

 Extruded aluminum, adjustable linear slot diffuser

Finish:

- Arctic White Border and Center Tees,
 Black Volume / Pattern Controllers
- Optional Anemostat Color
- Custom Color Match

MODELS

Supply Diffusers

FF-CM-250 2-1/2" Slot Width,


Concealed Mounting

Returns (No Volume / Pattern Controllers)

FFR-CM-250 2-1/2" Slot Width,


Concealed Mounting

SINGLE SLOT



FFCM-250 (2-1/2" SLOT WIDTH)						
# OF SLOTS	С	D	Е	G	Н	J
1	5-5/16	5-5/16	5-5/8	3-5/32	1-13/32	-
2	10-5/16	10-5/16	10-5/8			2-1/2
3	15-5/16	15-5/16	15-5/8			2-1/2
4	20-5/16	20-5/16	20-5/8			

MULTIPLE SLOT (FRAME OPENING) OPTIONAL PLENUM +1/16 DUCT OPENING (BY ANEMOSTAT) CEILING FRAMING (BY OTHERS) REVERSIBLE MOUNTING TAB FOR 5/8" OR 7/8" APPLICATION OR Н 1/16" FOR TAPE AND FEATHERING FLUSH TO C + 2-1/2 FINISHED CEILING SHEET ROCK/PLASTER (BY OTHERS)



All dimensions are in inches.

SUBMITTED BY: