


www.anemostat-hvac.com



Model GC5

GRID CORE RETURN

1/2" X 1/2" X 1/2" (13 X 13 X 13) CORE SURFACE MOUNTED 0° CORE

SUBMITTAL SHEET

PRODUCT FEATURES CONSTRUCTION DETAILS Accessories • 1/2" x 1/2" x 1/2" (13 x 13 x 13) □ ов Material: Extruded Aluminum Frame (std) Opposed Blade Damper aluminum core Finish: · Registers include a factory attached, Arctic White (std) steel opposed blade volume control ☐ Custom Color (opt) damper · Surface mounting holes in frame neatly countersunk for supplied #8 x 1-1/4" (32) oval head screws 29/32 (23)3/16 1/2 X 1/2 X 1/2 (13 X 13 X 13) ALUM. GRID CORE C'SUNK SCREW HOLES 1/8 (3) TYP. 5/16 (8) NOMINAL DUCT HEIGHT + 1 3/4 (45) NOMINAL DUCT SIZE 0 1/8 (3) 1 7/32 (31)3 5/32 (80) TYP. NOMINAL DUCT WIDTH + 1 3/4 (45) OPTIONAL ⁻ OPPOSED BLADE **VOLUME DAMPER** (OBD) All dimensions are in inches. JOB NAME: **SUBMITTED BY:**