

USGBC AND LEED PROGRAM

www.anemostat-hvac.com

Anemostat continues to support the use of sustainable building products and the development of creative solutions to today's challenges in indoor air quality and building environment. The original "Anemostat" was a device designed to improve the space condition, providing a healthy and comfortable environment. The tradition continues today.

The Leadership in Energy and Environmental Design (LEED) Green Building Rating System[™] is the nationally accepted benchmark for the design, construction and operation of high performance green buildings, those projects that are environmentally responsible, profitable and a healthy place to work. LEED qualified projects are increasing as a percentage of commercial construction projects. Owners, Architects, Engineers and Contractors view "GREEN" construction as a concept that continues to grow in acceptance and design.

Numerous Anemostat Products can assist a building project in obtaining LEED™ points in the Green Building Rating System. Below are some suggestions as to how use of Anemostat Products may qualify a project with respect to various sections of LEED V4-NC.

Please contact us to discuss your particular design concerns.

Energy & Atmosphere

· Optimize Energy Performance

Reduce energy cost compared to ASHRAE 90.1 - Energy Standard for buildings except low-rise residential buildings

ECM motors on Fan Terminals

Variable Air Volume Systems

Install continuous metering equipment for end users

Constant and Variable volume terminals with airflow measuring via the

Velocity Wing ™Sensor

Retrofit measuring station (RF-7) with Velocity Wing ™Sensor

Material & Resources

Use of building materials and products manufactured within 100 miles.
 Anemostat products are manufactured in Carson, CA.

Extend the life cycle of existing building stock, conserve resources, reduce waste and reduce environmental
impacts of new buildings. If project is a renovation points are awarded on basis of maintaining existing walls, floors
and roofs.

VAV Retrofit Products
Air Distribution Products, Grille, Registers and Diffusers



USGBC AND LEED PROGRAM

www.anemostat-hvac.com

Indoor Environmental Quality

· Building complies with ASHRAE 62.1

Many Anemostat products are available with double wall construction, foil faced, elastomeric closed cell foam, or fiberglass insulation with a 4lb. density liner.

Water based, glue used to secure insulation to unit walls

 Provide for the effective delivery and mixing of fresh air to support the safety, comfort and well being of building occupants.

Model DU dual duct VAV terminals

Flow measuring on supply and exhaust VAV terminals with retrofit measuring station. Variety of air distribution devices with high rate of air change capability

 Reduce the quantity of indoor air contaminants that are odorous, potentially irritating and/or harmful to the comfort and well being of installers and occupants. Specify low VOC paints and coatings.

> Powder coat painted products Water base adhesives Closed cell foam insulation Foil Insulation

 Provide controls for each individual for airflow, temperature and lighting for at least 50% of the occupants in non-perimeter regularly occupied areas.

VAV diffusers

Zone control through VAV systems

 Thermal Comfort, Compliance with ASHRAE 55 for thermal comfort standards including humidity control within established ranges per climate zone.

> Air Distribution Products which can be selected utilizing ADPI Zone Control through use of VAV Systems

Innovation & Design Process

 For exceptional performance above LEEDS requirements, or innovative performance in Green Building categories not addressed by the LEED Rating System. Items that are quantifiable and have an impact on either health or environmental issues.

A tradition of innovation in product design and application.

A willingness to push boundaries and effect change

"Anemostat the first name in air diffusion"