model MV-1

Single Chamber Laminar Flow Panels

features at a glance

MODEL

- ❑ **MV-1** - MULTI-VENT SINGLE CHAMBER LAMINAR FLOW PANEL

INSTALLATION

- ❑ LAY-IN T-BAR GRID SYSTEM
- ❑ SURFACE / HARD CEILING (SPECIFY BATTEN ARRANGEMENT PAGE A-33)
- ❑ INACTIVE PERFORATED PANEL TO MATCH ACTIVE PANELS
- ❑ BLANK-OFF PANEL (SOLID)

NOMINAL WIDTH

- ❑ 8"
- ❑ 12"
- ❑ 24"
- ❑ 36"

NOMINAL LENGTH

- ❑ 2'
- ❑ 3'
- ❑ 4'
- ❑ 5'
- ❑ 6'

TOP INLET SIZE

- ❑ 4" - 5" Ø (8" WIDE UNITS)
- ❑ 4" - 9" Ø (12" WIDE UNITS)
- ❑ 4" - 18" Ø (24 & 36" WIDE UNITS)

MATERIAL AND FINISH

DISTRIBUTION PANEL

- ❑ STEEL WITH WHITE BAKED EPOXY
- ❑ ALUMINUM WITH WHITE BAKED EPOXY
- ❑ 304 STAINLESS STEEL, #4 POLISH
- ❑ 304 STAINLESS STEEL WITH WHITE BAKED EPOXY

PLENUM

- ❑ STEEL WITH WHITE BAKED EPOXY
- ❑ ALUMINUM WITH WHITE BAKED EPOXY
- ❑ 304 STAINLESS STEEL, 2B MILL FINISH
- ❑ 304 STAINLESS STEEL WITH WHITE BAKED EPOXY

FOR ALUMINUM ANODIZED FINISHES, CONTACT FACTORY.

ACCESSORIES

- ❑ 1/2" FOIL FACED EXTERNAL INSULATION