



- MODEL**
- QSTS - Basic Assembly
 - QSTW - with Hot Water Heating Coils
 - QSTE - Electric Heating Coils

- INLET SIZE**
- 6" Ø
 - 7" Ø
 - 8" Ø
 - 9" Ø
 - 10" Ø
 - 12" Ø
 - 14" Ø
 - 16" Ø

- MOTOR HORSEPOWER**
- 1/6 HP
 - 1/4 HP
 - 1/2 HP
 - 3/4 HP
 - 1 HP

- FAN MOTOR VOLTAGE**
- 120 Volt / 1 Phase
 - 277 Volt / 1 Phase

- FAN SPEED CONTROL**
- SCR Controller

- CASING CONSTRUCTION**
- Galvanized Steel 20 Gauge

- CASING TREATMENTS**
- 1" Matte Insulation
 - 1/2" Foil Faced Insulation
 - 1" Foil Faced Insulation
 - 3/8" Fiber-Less Insulation
 - Dual Wall
 - Lo-Temp

- CONTROL SYSTEM**
- Pneumatic Controls
 - Electronic Analog Controls
 - Direct Digital Controls (DDC)
 - Electric Controls
- Control strategies available for all applications

- CONTROL SIDE**
- Left Side

- REHEAT OPTIONS**
- 1 Row Hot Water Coil
 - 2 Row Hot Water Coil
 - Electric Coil (L.H. connection only)
-
- Right Hand Connection
 - Left Hand Connection

- ELECTRIC COILS**
- 120 Volts
 - 208 Volts
 - 240 Volts
 - 277 Volts
 - 480 Volts
-
- 1 Phase
 - 1 Step
 - 2 Step
 - 3 Phase
 - 3 Step
-
- Door Interlocking Disconnect Switch, Non-Fused
 - Power Fusing
 - Primary Fused Transformer
 - Manual Reset Secondary Thermal Cutout
 - Air Proving Switch

- ACCESSORIES**
- ACCESS DOORS**
- Bottom
-
- CASING OPTIONS**
- Unit Mounting Bracket (shipped loose)
 - Manual Damper Locking
 - Standard Control Enclosure
 - Hinged Front Panel (control enclosure)
 - Discharge Collar, Slip & Drive
 - 1" Throw Away Filter
- ELECTRIC CONTROLS**
- Control Transformer
 - Low Voltage Control Disconnect Switch
 - Low Voltage Fuse & Fuse Block
 - Low Voltage Disconnect Switch
 - Low Voltage Power-Fusing
 - 24 VAC Actuator
 - Fan Relay, 24 VAC