

SUBMITTAL SHEET

www.anemostat-hvac.com

OPPOSED BLADE DAMPER

KEY OPERATED

PRODUCT FEATURES CONSTRUCTION DETAILS · Key operated volume control damper - face / front operated Material: Coated Steel (Standard) Aluminum (Stainless Steel Tension Wire) · Low pressure damper for balancing airflow through air inlets and outlets 304 Stainless Steel (Stn Steel Tension Wire) • Adjustable using 5/32" Hex Allen key or Slotted screwdriver (not included) Finish: Factory Choice (Standard) · Ribbed damper blades tensioned with wire to hold position and prevent rattling Flat Black • Maximum Width x Height = 24" x 24" (multiple dampers used for larger sizes) Arctic White · Specify use if separate from product Custom Color TENSIONING WIRE **FULL OPEN DAMPER ADDS** +2-1/8 TO GRILLE / 1/2 **DIFFUSER NECK HEIGHT GRILLE / DIFFUSER NECK OPFRATOR** 2-5/8 5/32 HEX ALLAN KEY OR SLOTTED SCREWDRIVER **FULL OPEN** NOM HEIGHT - 1/4 - NOM WIDTH - 1/4 --2-1/4 -All dimensions are in inches. JOB NAME: **SUBMITTED BY:**