



Cores are removable

PRODUCT FEATURES

- Extruded aluminum construction
- (7) Cores to choose from for appearance and deflection angle
- Removable core is standard on heights to 18"
- Non-removable core on heights over 18" (welded)
- Double deflection option includes rear louvers (individually adjustable) for spread control

AL1*
SINGLE DEFLECTION

DEFLECTING BAR 0° STANDARD

AL2*
DOUBLE DEFLECTION (Spread Control)

AL15*
SINGLE DEFLECTION

DEFLECTING BAR 15° STANDARD

AL25*
DOUBLE DEFLECTION

AL45*
SINGLE DEFLECTION

DEFLECTING BAR 45° STANDARD

PENCIL PROOF

TL1W
SINGLE DEFLECTION

DEFLECTING BAR 0° THINLINE

TL2W
DOUBLE DEFLECTION

TL15W
SINGLE DEFLECTION

DEFLECTING BAR 15° THINLINE

TL25W
DOUBLE DEFLECTION

TL1N*
SINGLE DEFLECTION

DEFLECTING BAR 0° THINLINE

TL2N*
DOUBLE DEFLECTION

TL15N*
SINGLE DEFLECTION

DEFLECTING BAR 15° THINLINE

PENCIL PROOF

TYPICAL CORE ASSEMBLY

Core cross bars are on 10" centers for AL style cores, 5" centers for TL style cores. Cross bars are 5" centers for all cores used with floor reinforcement.

*PENCIL PROOF: Models AL1, AL2, AL15, AL25, AL45, AL245, TL1N, TL2N, TL15N, TL25N are pencil proof

All dimensions are in inches.

JOB NAME:

SUBMITTED BY:

F

Product information is subject to change without notice.
Drawing is not to scale.

DWG# AL-S-0032 Date 11-12-13