



SPIRAL DUCT GRILLES
SINGLE DEFLECTION
3/4" LOUVER SPACING

www.anemostat-hvac.com

PRODUCT FEATURES	CONST	TRUCTION DETAILS	Louvers:
Adjustable supply grille for installation	Material:	20 GA Cold Rolled Steel Frame (std)	Horizontal
into spiral duct		iteel	Vertical
Durable Arctic White finish	A	luminum	Volume Damper:
• 3/4" Louver Spacing	Finish: A	Arctic White (std)	None
Louvers independently adjustable		Custom Colors (opt)	☐ Diverter (must be factory installed)
<ul> <li>Screws &amp; screw holes in outer frame provided</li> </ul>			
Frame Gasketing			
Mo	odel ECO1	0, Blade Direction Long (L) Sh	own
SIZE AVAILABILITY		L- NOMIN	IAI WIDTH
NOM GRILLE		NOMIN	AL WIDTH
WIDTH 6" TO 48"		į	OPTIONAL
NOM. GRILLE   3"   4"   6"   8"   10"   12"	14" 16" 18"	AIR FLOW DIRECTION	DIVERTING DAMPER
MINIMUM F. C. O. 10. 14. 10.	20" 24" 26"	<u> </u>	
DUCT DIAMETER 5 6 8 12 14 18	20 24 20	<u> </u>	
		¦	<u></u>
		i <u> </u>	i
2-1/2 —			5/32 FEMALE
			HEX HEAD
	-1/4		
3/16	<del>-</del>	1-1/4	
		<u>.</u> . ⊚	©
	+	34 SPACING TYP.	
NOTE: For single and double	Ţ	NI	3/4 –
deflection with horizontal face louvers, Anemostat	11/16	SPAC	+ <u>E</u>
will provide front louvers that follow the curvature of	÷	9/8	BHT TAME
the duct (Architect's Choice).  Support mullions used	EIG	•	
deflection with horizontal face louvers, Anemostat will provide front louvers that follow the curvature of the duct (Architect's Choice).  Support mullions used on widths 20" and longer.	NOM. HEIGHT - 11/16		NOMINAL HEIGHT + 1-3/4 (APPROXIMATE)
	<u>N</u>	†	
<u>+</u>		⊚	©
DUCT	FRAME GASKET	NOMINAL V	NIDTH + 1-9/16 ────
DIAMETER			
//			
NOMINAL = DUCT OPENING			
HOMINAL - DOOT OF LINING			
			All dimensions are in inches.
JOB NAME:		SUBMITTED BY:	All differsions are in inches.
		· = =	