

SUBMITTAL SHEET

www.anemostat-hvac.com

Model FF-V-200 Free Flo

ARCHITECTURAL LINEAR
SLOT DIFFUSER

2" SLOT WIDTH

CONCEALED / BORDERLESS FRAME (V)

PRODUCT FEATURES CONSTRUCTION FEATURES **SUPPLY MODELS** Concealed frame for use with tile, masonry, & millwork surfaces. For GWB applications, use Border BF (Mud-In Frame) Material: Extruded Aluminum FF-V-200 2" Slot Width Finish: **RETURN MODELS** (No Internal Controllers) · Adjustable volume and pattern controllers Arctic White Outer Frame · Hardware package includes duct mounting FFR-V-200 2" Slot Width brackets & screws, and alignment strips (where a (Black Pattern/Volume Controllers) continuous run consists of multiple sections) Gloss Black - Outer Frame & Pattern **OPTIONS** Anemostat Model AD-X plenums are ordered and / Volume Controllers shipped separate from the diffusers. Contact AD Engineered Air Distribution Plenum Custom Color : factory for plenum details for this model. LEC Linear Egg Crate · Nominal Length is the order size LED Linear Equalizing Deflector · Flush end caps are removable All dimensions are in inches. 4-5/16 3-13/16 3-9/16 MODEL AD-X ENGINEERED PLENUM (OPTIONAL) **DUCT MOUNTING BRACKETS & SCREWS ADJUSTABLE** PATTERN / VOLUME CONTROLLERS 2-21/32 1-3/16 1-3/16 RANGE = 1-5/8 TO 1-1/2 2-1/4 45° 1/2" CEILING T5 **MOUNTING** 5/8" CEILING -**MOUNTING MATERIAL** TABS 3-13/16 **MATERIAL TABS** (OPTIONAL) (OPTIONAL) - 1/16 NOM LENGTH FLUSH END CAPS OPTIONAL T4/T5 MOUNTING TABS (FACTORY INSTALLED) JOB NAME: SUBMITTED BY: