





www.anemostat-hvac.com

PRODUCT FEATURES CONSTRUCTION DETAILS Models ☐ **HD30** 3/4" Blade Spacing Material: • 1/2" or 3/4" Blade spacing · Registers include a factory attached steel ☐ Steel Construction HD35 1/2" Blade Spacing opposed blade volume control damper ☐ 304 SS Construction 0° Deflection · Surface mounted holes in frame neatly Finish: 40° Deflection countersunk for supplied #8 x 1-1/2" oval Arctic White (std) head screws **Accessories** ☐ Custom Color (opt) • 16 GA Steel Frame / 14 GA Support Bars OB-1 Opposed Blade Damper · Heavy-Duty Blades 0° DELECTION SHOWN SUPPORT BARS 1-7/8 LONG BLADES SHOWN (L) 0 NOM DUCT - 11/16 NOM DUCT + 1-13/16 NOMINAL -DUCT SIZE 0 0 6" MAX **TYPICAL OPTIONAL** NOM DUCT + 1-13/16 OPPOSED BLADE DAMPER (FACTORY ATTACHED) SHORT BLADES (S) 0° DELECTION, 1/2" SPACING 40° DELECTION, 1/2" SPACING All dimensions are in inches. JOB NAME: **SUBMITTED BY:**