



PLENUM SLOT CEILING RETURN 9/16" LAY-IN T-BAR

www.anemostat-hvac.com

MODELS PRODUCT FEATURES CONSTRUCTION DETAILS • 1,2,3, or 4 parallel slots integrated Material: 24 GA Zinc-Coated Steel SCR-L9 All center Tees included into a coated steel plenum for return Finish: Flat black on exposed SCR-L9-N 2' x 2' Crossover, Diffuser Face surfaces (std) All center Tees included Factory attached T-Bars are white · Matching return for Model SCD (notch in center of 4' plenum) Supply Diffuser SCR-L9X Straddle (2 slot only - NO center ☐ Custom Colors (opt) • 3/4", 1", 1-1/2" slot widths Tee). Unit includes notched end · 24", 36", 48", 60" nominal lengths caps for grid member. SCR-L9X-N Combination Crossover and Straddle feature (2 slot only) 2 SLOT WITH 2 SLOT WITH **FACTORY CENTER TEE** STRADDLE FEATURE SHOWN SHOWN INTERNAL INSULATION (OPTIONAL) OPTIONAL CROSS NOTCH FOR N CROSSOVER APPLICATIONS NOMINAL LENGTH - 1/4 T-BAR BY OTHERS NOMINAL LENGTH CENTER T-BARS, NOTCH STANDARD ON 3 & 4 SLOT OPTIONAL ON 2 SLOT **SLOT** В **WIDTH** 1-SLOT 2-SLOT 3-SLOT 4-SLOT NOM LENGTH Α OPTIONAL STRAFF SCR-75 3/4' 5-1/4 1-3/4 3-1/2 7 **SCR-10** 1" 2 4 6 8 24, 30, 36, 48, 60 **SCR-15** 1-1/2" 2-1/2" 5 7-1/2 10 OPTIONAL N CROSS NOTCH FOR CROSSOVER APPLICATIONS 5/16 TYPICAL 2 SLOT INSTALLATION ■ & N

JOB NAME:

NOTCH DETAIL

SUBMITTED BY:

All dimensions are in inches.



Model SCD

ADJUSTABLE
PLENUM SLOT DIFFUSER
ACCESSORIES & OPTIONS

FACTORY INSTALLED SIDE TEES / CLIPS (FACTORY TEES ARE 1" WIDE - WHITE FINISH) OPTION 1 OPTION 2 OPTION 3 ONE SIDE TEE TWO SIDE TEE ONE SIDE TEE (INLET SIDE) (NON-INLET SIDE) OPTION A OPTION B OPTION C T-BAR CLIPS ONE SIDE TEE ONE SIDE TEE (INLET SIDE) (BOTH SIDES) (NON-INLET SIDE) + T-BAR CLIPS + T-BAR CLIPS **GRID / CEILING TYPE** 15/16 9/16 15/16" LAY-IN 9/16" LAY-IN 9/16" TEGULAR 9/16" NARROW SLOT CEILING MANUFACTURER: ___ Z = ____ MODEL: _____ All dimensions are in inches.

JOB NAME:

SUBMITTED BY: