MODEL
- ❑ **EZTS** - Basic Assembly
- ❑ **EZTA** - with Integral Sound Attenuator
- ❑ **EZTE** - wIth Integral Electric Heat

INLET SIZE
- ❑ 5" Ø
- ❑ 6" Ø
- ❑ 7" Ø
- ❑ 8" Ø
- ❑ 9" Ø
- ❑ 10" Ø
- ❑ 12" Ø
- ❑ 14" Ø
- ❑ 16" Ø
- ❑ 24"x16"

CASING CONSTRUCTION
- ❑ Galvanized Steel
- ❑ 304 Stainless Steel
- ❑ 316 Stainless Steel

- ❑ 22 Gauge
- ❑ 20 Gauge

CASING TREATMENTS
- ❑ 1/2" Matte Insulation
- ❑ 1" Matte Insulation
- ❑ 1/2" Foil Faced Insulation
- ❑ 1" Foil Faced Insulation
- ❑ 1" Fibre-Lok Insulation
- ❑ 3/8" Fiber-Less Insulation
- ❑ Dual Wall
- ❑ Lo-Temp

CONTROL SYSTEM
- ❑ Pneumatic Controls
- ❑ Electronic Analog Controls
- ❑ Direct Digital Controls (DDC)
- ❑ Electric Controls

Control strategies available for all applications

CONTROL SIDE
- ❑ Right Side
- ❑ Left Side

REHEAT OPTIONS
- ❑ 1 Row Hot Water Coil
- ❑ 2 Row Hot Water Coil
- ❑ 4 Row Hot Water Coil
- ❑ Electric Coil

- ❑ Right Hand Connection
- ❑ Left Hand Connection

ELECTRIC COILS
- ❑ 120 Volts
- ❑ 277 Volts
- ❑ 208 Volts
- ❑ 480 Volts
- ❑ 240 Volts

- ❑ 1 Phase
- ❑ 3 Phase

- ❑ 1 Step
- ❑ 3 Step
- ❑ 2 Step

- ❑ Door Interlocking Disconnect Switch, Non-Fused
- ❑ Power Fusing
- ❑ Primary Fused Transformer

ACCESSORIES

ACCESS DOORS
- ❑ Bottom
- ❑ Side

- ❑ Patch Plate
- ❑ Hinged Camlock
- ❑ Double Camlock

CASING OPTIONS
- ❑ Unit Mounting Bracket (shipped loose)
- ❑ Manual Damper Locking
- ❑ Standard Control Enclosure
- ❑ Large Control Enclosure
- ❑ Hinged Front Panel (control enclosure)
- ❑ Lo-Leakage Casing

ELECTRIC CONTROLS
- ❑ Control Transformer
- ❑ Low Voltage Control Disconnect Switch
- ❑ Low Voltage Fuse & Fuse Block
- ❑ Low Voltage Disconnect Switch
- ❑ Low Voltage Power-Fusing
- ❑ 24 VAC Actuator