MODEL

- ❑ **HCRF** - HIGH CAPACITY RADIAL FILTER MODULE

AIR DISTRIBUTION PATTERN

- ❑ 90 DEGREE
- ❑ 180 DEGREE

INSTALLATION

- ❑ LAY-IN T-BAR GRID SYSTEM
- ❑ SURFACE / HARD CEILING (SPECIFY BATTEN ARRANGEMENT PAGE A-33)

NOMINAL SIZE

- ❑ 12" X 48"
- ❑ 24" X 24"
- ❑ 24" X 48"

TOP INLET SIZE

- ❑ 5" - 9" Ø (12" WIDE UNITS)
- ❑ 4" - 18" Ø (24" WIDE UNITS)

MATERIAL AND FINISH

DISTRIBUTION PANEL	DUAL CHAMBER PLENUM
❑ STEEL WITH WHITE BAKED EPOXY	❑ STEEL WITH WHITE BAKED EPOXY
❑ ALUMINUM WITH WHITE BAKED EPOXY	❑ ALUMINUM WITH WHITE BAKED EPOXY
❑ 304 STAINLESS STEEL, #4 POLISH	❑ 304 STAINLESS STEEL, 2B MILL FINISH
❑ 304 STAINLESS STEEL WITH WHITE BAKED EPOXY	❑ 304 STAINLESS STEEL WITH WHITE BAKED EPOXY

CONTACT FACTORY FOR ANODIZE OPTIONS

ACCESSORIES

- ❑ LIGHT-ALERT FILTER LOADING SENSOR
- ❑ 1/2" FOIL FACED EXTERNAL INSULATION