

## MINIMUM SECURITY

### Non-Vision DOOR GRILLE Lattice Face Plate

#### STANDARD FEATURES

- FACE PLATE: 12 GA C.R.S. Lattice Face Plate and Security Grille - 13/16" square holes on 1" centers
- LOUVER BLADES: 18 GA C.R.S.
- FASTENERS: #8 x 32 Phillips head thru bolts with blank head one side
- FREE AIR FLOW: 50% free area

#### FINISH

- STANDARD: White Powder Coat Finish
- OPTIONAL: Consult factory for other finishes

#### OPTIONAL FEATURES

- MATERIAL: #304 or #316 stainless steel, #4 finish (satin), hot dipped or zinc plated galvanized
- TAMPERPROOF SCREWS: See inside back cover, page i, and consult factory for specific product applications
- WIRE SCREEN: galvanized, aluminum, charcoal aluminum, stainless steel, attached or framed

#### CONSTRUCTION

The PLSL is a non-vision inverted split "Y" door louver constructed of all steel components (see options) with a removable lattice face security plate.

#### INSTALLATION

The PLSL is installed into the door cutout (1-3/8" minimum thickness/ 2-1/4" maximum) by drilling holes through the door to accommodate #8-32 phillips head thru bolts, with a blank head one side (other tamperproof screws optional), to secure the two louver assemblies to the door. Optional insect screen is available loose or attached.

